

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number
WO 03/089805 A2

(51) International Patent Classification⁷: **F16F 7/12**,
B60R 19/34

(21) International Application Number: PCT/US03/11908

(22) International Filing Date: 17 April 2003 (17.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/373,607 19 April 2002 (19.04.2002) US

(71) Applicant (*for all designated States except US*): **MAGNA INTERNATIONAL INC.** [—/CA]; 337 Magna Drive, Aurora, Ontario L4G 7K1 (CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **LONGO, Thomas, W.** [US/US]; 13267 Tonabee Drive, Sterling Heights, MI 48313 (US).

(74) Agent: **MCBETH, Robert, F.**; Patent Counsel, Magna International of America, Inc., Troy, MI 48084 (US).

(54) Title: COLLISION ENERGY-ABSORBING DEVICE

(57) Abstract: A collision energy-absorbing device includes a body member connected between the frame assembly of a motor vehicle and a bumper beam. The body member collapses as the bumper beam and the frame assembly are moved relatively toward one another during a vehicle collision. The body member has a first telescoping portion and a second telescoping portion that are connected by a connecting portion. The telescoping portions have different cross-sectional dimensions to enable the telescoping portions to move one within the other into collapsing telescoping relation as the body member collapses with the connecting portion being deformed and received between the telescoping portions. One or more protrusions extending from one of the telescoping portions interfere with relative movement of the other of the telescoping portions to retard movement of the telescoping portions into telescoping relation.

WO 03/089805 A2